

LIGHT COMMERCIAL RO SYSTEM



Specification

Model	11-ROC-100	11-ROC-200	11-ROC-300	11-ROC-400
Production Rate	100 GPD	200 GPD	300 GPD	400 GPD
Membrane Element	2x 50 GPD	2x 100 GPD	3x 100 GPD	3x 150 GPD
Operation Pressure	10-90 PSI	10-90 PSI	10-90 PSI	10-90 PSI
Operation Temperature	40-110°F	40-110°F	40-110°F	40-110°F
System Dimension	30"x18"x9"	30"x18"x9"	32"x18"x9"	32"x18"x9"
System Weight	46 lbs	46 lbs	48 lbs	53 lbs

Please allow one week lead time



Tank and System must be ordered separately

Standard Features:

1. 5 micron sediment pre-filter, 20"
2. 10 micron carbon block pre-filter, 20"
3. TFC membranes
4. Post-filter, coconut GAC, 20"
5. High flow booster pump
6. Free standing powder coated aluminum alloy frame

Optional Features:

1. Permeate pump add-on: fills product tank faster and saves waste water
2. Tank optional: 14 gallon, 20 gallon, 34 gallon, 44 gallon, 82 gallon
3. UV light add-on: for well water application

Call 1-800-242-7769